

EDS-205/208 Series

5 and 8-port entry-level unmanaged Ethernet switches



- > 10/100BaseT(X) (RJ45 connector), 100BaseFX (multi-mode, SC/ST connectors)
- > IEEE802.3/802.3u/802.3x support
- > Broadcast storm protection
- > DIN-Rail mounting ability
- > -10 to 60°C operating temperature range



Introduction

The EDS-205/208 series of industrial Ethernet switches are entry-level industrial 5 and 8-port Ethernet switches that support IEEE 802.3/802.3u/802.3x with 10/100M, full/half-duplex, MDI/MDIX auto-sensing RJ45 ports. The EDS-205/208 switches are rated to operate at temperatures ranging from -10 to 60°C, and are rugged enough for

any harsh industrial environment. The switches can be easily installed on a DIN-Rail as well as in distribution boxes. The DIN-Rail mounting capability, wide operating temperature, and the IP30 housing with LED indicators make the plug-and-play EDS-205/208 switches easy to use and reliable.

Specifications

Technology

Standards:

IEEE 802.3 for 10BaseT
IEEE 802.3u for 100BaseT(X) and 100BaseFX
IEEE 802.3x for Flow Control

Processing Type: Store and Forward

Flow Control: IEEE 802.3x flow control, back pressure flow control

Interface

Fiber Ports: 100BaseFX ports (SC/ST connector, multi-mode)

RJ45 Ports: 10/100BaseT(X) auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection

LED Indicators: Power, 10/100M (TP port), 100M (fiber port)

Optical Fiber

	100BaseFX	
	Multi-mode	Single-mode
Wavelength	1300 nm	1310 nm
Max. TX	-10 dBm	0 dBm
Min. TX	-20 dBm	-5 dBm
RX Sensitivity	-32 dBm	-34 dBm
Link Budget	12 dB	29 dB
Typical Distance	5 km ^a 4 km ^b	40 km ^c
Saturation	-6 dBm	-3 dBm

a. 50/125 μm, 800 MHz*km fiber optic cable
b. 62.5/125 μm, 500 MHz*km fiber optic cable
c. 9/125 μm single-mode fiber optic cable

Power Requirements

Input Voltage:

EDS-205: 12 to 48 VDC, 18 to 30 VAC (47 to 63 Hz)
EDS-208 series: 12 to 45 VDC, 18 to 30 VAC (47 to 63 Hz)

Input Current:

EDS-205: 0.12 A @ 24 V
EDS-208: 0.14 A @ 24 V
EDS-208-M: 0.23 A @ 24 V

Overload Current Protection: 1.1 A

Connection: 1 removable 3-contact terminal block

Reverse Polarity Protection: Present

Physical Characteristics

Housing: Plastic, IP30 protection

Dimensions:

EDS-205: 25 x 100 x 74 mm (0.98 x 3.94 x 2.91 in)
EDS-208: 40 x 100 x 74 mm (1.57 x 3.94 x 2.91 in)

Weight:

EDS-205: 135 g
EDS-208: 170 g

Installation: DIN-Rail mounting

Environmental Limits

Operating Temperature: -10 to 60°C (14 to 140°F)

Storage Temperature: -40 to 85°C (-40 to 185°F)

Ambient Relative Humidity: 5 to 95% (non-condensing)

Regulatory Approvals

Safety:

EDS-205: UL508
EDS-208: UL508, UL60950-1

EMI: FCC Part 15, CISPR (EN55022) class A

EMS:

EN61000-4-2 (ESD), level 2
 EN61000-4-3 (RS), level 3
 EN61000-4-4 (EFT), level 3
 EN61000-4-5 (Surge), level 3
 EN61000-4-6 (CS), EDS-205: level 3; EDS-208: level 2
 EN61000-4-8
 EN61000-4-11

Shock: IEC 60068-2-27

Freefall: IEC 60068-2-32

Vibration: IEC 60068-2-6

Note: Please check Moxa's website for the most up-to-date certification status.

MTBF (meantime between failures)

Time:

EDS-205: 323,000 hrs

EDS-208: 368,000 hrs

Database:

EDS-205: Telcordia (Bellcore), GB


EDS-208: MIL-HDBK-217F, GB 25°C

Warranty

Warranty Period: 5 years

Details: See www.moxa.com/warranty

Dimensions (unit = mm)



: Ordering Information

Available Models	Port Interface			Housing Material	Power Range
Standard Temperature (-10 to 60°C)	10/100BaseT(X)	100BaseFX			
		Multi-mode, SC Connector	Multi-mode, ST Connector		
EDS-205	5	---	---	Plastic	12 to 48 VDC
EDS-208	8	---	---	Plastic	12 to 45 VDC
EDS-208-M-SC	7	1	---	Plastic	12 to 45 VDC
EDS-208-M-ST	7	---	1	Plastic	12 to 45 VDC

Optional Accessories (can be purchased separately)

DR-4524/75-24/120-24: 45/75/120 W DIN-Rail 24 VDC power supplies

RK-4U: 4U-high 19" rack mounting kit