

HDMI/Audio Cat 5 Extender with MK Wall Plate

VE807

- The VE807 HDMI/Audio Cat 5 Extender with MK Wall Plate is designed to be conveniently mounted in a one- gang junction box for the UK, Singapore, Hong Kong and other markets that apply MK type junction boxes. It extends HDMI and audio signals up to 60 meters over a Cat 5e cable and supports widescreen formats ensuring excellent video quality.

The VE807 can be easily powered at either the transmitter or receiver side using a second Cat 5e cable. The VE807's compact wall plate design does away with bulky cables allowing a neat and convenient installation. Therefore, it is a perfect solution for function rooms, museums and any setting that requires equipment or cabling to be kept from the public's view.



HDMI™
HIGH DEFINITION MULTIMEDIA INTERFACE




Features

- Uses two Cat 5e cables to connect the local and remote units- one to transmit video and another to supply power*
- Remotely powered from either the transmitter or receiver side**
- Extends the distance between HDMI source and display
- Supports superior video quality up to 1080p @ 60 Hz at a distance of 40 m; 1080i @ 60 Hz at a distance of 60 m
- Designed to mount in one- gang junction box for UK, Singapore, Hong Kong and other markets that apply MK type junction boxes.
- HDMI (3D, Deep Color); HDCP compatible
- Supports 8 segment equalization adjustment via switch
- Supports wide screen formats
- Supports hot- plugging
- Supports stereo audio
- Built-in 8KV/ 15 KV ESD protection
- Plug- and- play with no software installation required
- LED indication of power sources / connection status

* A second Cat 5e cable connection is required to remotely power on either the transmitter or receiver

**A power adapter is provided with this package and can be used at either the transmitter or receiver side, which in turn remotely powers the other unit



Specifications

Function	VE807R	VE807T
Video Input		
Interfaces	N/A	1 x HDMI Type A Female (Black)
Impedance	N/A	100 Ω
Max. Distance	N/A	1.8 m
Video Output		
Interfaces	1 x HDMI Type A Female (Black)	N/A
Impedance	100 Ω	N/A
Video		
Max. Data Rate	6.75 Gbps (2.25 Gbps Per Lane)	
Max. Pixel Clock	225 MHz	
Compliance	HDMI (3D, Deep Color) HDCP Compatible	
Max. Resolutions / Distance	Up to 1080p@40m; 1080i@60m	
Audio		
Input	N/A	1 x HDMI Type A Female (Black)
Output	1 x HDMI Type A Female (Black)	N/A
Power		
Connectors	1 x Terminal Block (Green)	1 x Terminal Block (Green)
Consumption	9 VDC, 2.9 W	9 VDC, 2.9 W
Environmental		
Operating Temperature	0° to 50° C	
Storage Temperature	-20° to 60° C	
Humidity	0-80% RH, Non-Condensing	
Physical Properties		
Housing	Metal	Metal
Weight	0.16 kg	0.16 kg
Dimensions (L x W x H)	6.86 x 4.44 x 3.98 cm	6.86 x 4.44 x 3.98 cm

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com

Publish Date: 04/2017 V1.0



© Copyright 2017 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.