

Datenblatt Art. 800.2333

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

19" Steckdosenleiste 1HE

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung	16A / 250V~	Rated current / rated voltage	16A / 250V~
Frequenz	50 Hz	Frequency	50 Hz
Netzanschluss		Power supply	
Zuleitung	2,0m H05VV-F 3G1,5mm ²	Supply cable	2,0m H05VV-F 3G1,5mm ²
Farbe Zuleitung	Schwarz	Colour supply cable	Black
Stecker	IEC60320 C20	Plug	IEC60320 C20
Stromausgang		Power output	
Steckdosen		Socket outlets	
6x CEE 7/3 (Type F)		6x CEE 7/3 (Type F)	
2-polig mit Schutzkontakt		2-pole with earthing contact	
Mit erhöhtem Berührungsschutz		With shutter	
Rot, ähnlich RAL 3020, 35°		Red, similar to RAL 3020, 35°	
16A 250V~, IP20		16A 250V~, IP20	
3x IEC60320 C19		3x IEC60320 C19	
2-polig mit Schutzkontakt		2-pole with earthing contact	
Rot, ähnlich RAL 3020, 90°		Red, similar to RAL3020, 90°	
16A 250V~, IP20		16A 250V~, IP20	
Weitere Produkteigenschaften		Further product attributes	
Plattform	1 HE	Platform	1 HE
Material		Material	
Gehäuse:		Housing:	
Aluminium, eloxiert		Aluminium, anodised	
Abdeckung:		Cover:	
PA6 GF30 850°C, schwarz ähnlich RAL 9005		PA6 GF30 850°C, black similar to RAL 9005	
Lieferumfang		Scope of delivery	
1x 19" Steckdosenleiste 1HE ALU		1x 19" power strip 1HE ALU	
2x Haltewinkel und Schrauben		2x Mounting brackets and screws	
Im Karton		In carton	

Umgebungsbedingungen**Environmental conditions****Schutzart**

IP20

Protection type

IP20

BAN.-Nr.: BAN14564

